



SOLID GLUE RY/S COLOURED

Coloured solid polyester glue.
Suitable for gluing stone, marble, granite and onyx.

PRODUCT DESCRIPTION

Mastic for marble, granite, onyx and stones in thixotropic paste. Easily polishable once hardened. Good storage stability.

INSTRUCTION FOR USE:

Make sure that the part to be glued is dry, clean and free of dust. Take the desired quantity of mastic from the jar and add the catalyst paste in the quantity of 1-3% by weight. Do not put the unused glue back into the jar. If necessary color it use the coloring pastes. Add the dye before the catalyst.

PACKAGING:

KG1GW (ML750) – KG1.5GW (LT1) – KG6GW (LT4) – KG.25N (LT17)

SHELF LIFE

The product is guaranteed for 6 months if stored in a cool place, in its original packaging, away from sources of heat, light, humidity and sun light.

SAFETY RULES

Read Material Safety Data Sheet of the product before using it.

TECHNICAL DATA:

Aspect: Coloured paste

Density: 1.3 – 1.4 gr/ml

Ratio mix: 100 + 1-3%

Gel Time: 3-4 min

Minium temperature of use: 5°C

This information is drawn up on the basis of our best technical and application knowledge and are general indications that do not bind our company in any way. Each specific case must be subjected to a practical test by the user who assumes responsibility for the outcome of the work.

